

11

Smoother

ISUZU

ISU2U 275

Specification Sheet

NPR 275 AMT

www.isuzu.co.za f 🎔



MODEL	NPR 275 AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	3420
Tare – Total (T) (kg)	2380
Tare – Front (kg)	1560
Tare – Rear (kg)	820
GVM (kg)	5800
V (kg)	5800
GCM (kg)	9700
D/T (kg)	9700
Axle – Front GA/GAU (kg)	3100
Axle – Front A/AU (kg)	2900
Axle – Rear GA/GAU (kg)	6000
Axle – Rear A/AU (kg)	5600
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	
Gradeability at V (%)	37
Gradeability at D/T (%)	22
Max. Geared Road Speed (km/h)	103
MAJOR DIMENSIONS	
OL – Overall Length (mm)	5985
OW – Overall Width (mm)	1995
WB – Wheelbase (mm)	3365
CA – Cab to Bogie/Rear Axle (mm)	2792
CE – Cab to End of Chassis (mm)	3346
OH – Overall Height (mm)	2253
FOH – Front Overhang (mm)	1110
ROH – Rear Overhang (mm)	1585
EH – Chassis Rear End Height (mm)	828
HH – Ground Clearance (mm)	178

MODEL	NPR 275 AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
Chassis Width – Rear (mm)	850
Turning Radius – Curb to Curb (mm)	6400
Turning Radius – Wall to Wall (mm)	7150
ENGINE	
Make	lsuzu
Model	4JJ1-TC
Capacity (cm ³)	2999
Layout	Diesel Inline 4
Туре	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	96 @ 2800
Torque @ r/min (Nm)	330 @ 1600 – 2600
Emissions Standard	Euro 3
CLUTCH	
Make	N/A
Model	N/A
Туре	N/A
Diameter (mm)	N/A
Operation	Automated Hydraulic-Controlled Wet Clutch
TRANSMISSION	
Make	lsuzu
Model	MYY6S (AMT)
Туре	6-Speed Synchromesh
Shift	Automated Manual
No. of Gears Forward	6
First Gear Ratio : 1	5.979
Top Gear Ratio : 1	0.759
Transfer Case	No
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	lsuzu
Model Axle Front	F031

MODEL	NPR 275 AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
DRIVE AXLE	
Model Drive Axle Rear	R060
Reduction Type	Single
Final Ratio : 1	5.857
SUSPENSION	
Front	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs
Shock Absorbers	Front & Rear
Stabilisers	Yes
STEERING	
Operation	Power
BRAKES	
System Type	Vacuum Hydraulic
Front	Discs
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Drum on Propshaft
Exhaust Brake	Standard
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	100
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating – Front	215 / 75 R17.5
Size & Ply Rating – Rear	215 / 75 R17.5
CAB & EXTRAS	
Туре	Day
Roof	Low
No. of Bunks	0
No. of Seats (Lap Rear & Centre)	3
Air-Conditioning	Optional
Radio	Optional
Tilt Cab	Yes

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print December 2017